



SLIM BLOWER FIRST



SMART BLOWER WITH HOT AIR FLOW EXTRA-SLIM STYLE, ECODESIGN COMPLIANT FOR ELECTRIC TOWEL RAIL

Very thin controller with integrated blower, digital controls, programmable with opened window detection, gauge and power consumption indication in kWh, wireless remote control (optional)

Overview



ECOdesign 2018
compliant



Optional RF remote control

Main features

- Ambient temperature control
- Temperature setting
- Power On / Standby
- Operating modes selection
- Quick heating of the bathroom using the instant Boost
- Customized integrated programming or can be programmed remotely using the 6-order pilot wire

Application

- Electric towel rail
- Hydraulic towel rail

Benefits

- **Ultra-discreet** : Once integrated, the controller at the back of the heating body is aesthetically invisible
- **Adaptability** : can be mounted on electric or hydraulic device, and fits with different shapes of heating body, scale profile
- **Excellent ergonomic settings**
- **"Smart" electronic control**: this means stable and accurate temperature in the bathroom all year round
- **Energy Saving Pack**
- **Super comfort feature (automatic Boost)**: additional instantaneous heating, the hot air blower enables automatic and swift room temperature increase, after an Eco, Frost protection or Standby period
- **80 mm thickness behind the towel rail** : makes the packaging of towel rails easier and fits perfectly into small bathrooms
- **Active memory**: clock and settings are saved by EEPROM in case the mains power supply goes off

Functional specifications

Use



Power On / standby	A switch allows the appliance to be on standby
Temperature setting	Preset to +19°C, adjustable from +7°C to +30°C
Operating modes	Auto (programming), Comfort, Eco, Frost protection
Boost	Adjustable between 10 and 90 minutes in 5 minutes intervals: to rise quickly the temperature and turn on the blower for a time period requested
Energy consumption gauge	Automatic indication of the level of energy consumption according to the setting temperature
Power consumption indication in kWh	Posting of the estimated amount of energy consumed in kWh since the last 24 hours or since the last reset to 0 of the energy meter
Opened window detection	Automatic switching to Frost protection mode when a significant drop in temperature is detected
Window airing feature	Manual window airing can be enabled at any time
Programming	<ul style="list-style-type: none"> - 5 different preset program profiles for each day of the week : P1, P2, P3, non-stop Comfort mode, non-stop Eco (economy) mode - P1, P2, P3 programmes can be customised - Manual and temporary overriding of a programme



Safety	<ul style="list-style-type: none"> - Child anti-tamper : keypad locking - Settings safety : <ul style="list-style-type: none"> - Min. and Max limits of the adjustment range of the Comfort setting temperature - Customizable PIN code locking (prevents access to the Comfort mode, installer and expert settings) - Backup in case the mains power supply goes off : <ul style="list-style-type: none"> - The whole of settings and programming : permanent backup - Current time and date : backup time of 16hrs typical - Anti-obstruction safety: prevents the involuntary air flow obturations (filter and ventilation grid) shutting down/switching off the blower - Overheating protection of the ambient temperature during the Boost mode - Internal protection against any overheating
Tangencial turbine blower insuring a low noise level with anti vibration device, adjustable fins upwardly	
Removable anti-dust filter	Cleanable, without removing the blower
Post-ventilation	In order to preserve and improve the lifetime of the device, a post-ventilation cycle is performed after each boost or super comfort period to quickly decrease the internal temperature
3 levels of settings	User, Installer, Expert

Installation

Adaptability	Module adaptable to the majority of towel rails available on the market, straight, flat or curved tubes, 2 solutions for fixing the module to the heating body: <ul style="list-style-type: none"> - Towel rails with straight or curved tubes: 2 x wall-mounting brackets for 22mm diameter tubes (space between tubes: 42mm) and 25mm (space between tubes: 39mm) - Towel rails with flat tubes: 2 x M8 threaded shafts 	
Connection to the heating cartridge	Quick electric connexion by Faston	
Sealing	1 o'ring supplied	

User settings

Backlighting	2 settings: <ul style="list-style-type: none"> - Temporary backlighting (default setting): backlight of the screen when a button is pressed - Non-stop backlighting: backlight of the screen all the time
Eco mode temperature lowering level	Preset at -3,5°C , adjustable from -1°C to -8°C
Frost protection temperature	Preset at +7°C , adjustable from +5°C to +15°C
Super comfort (automatic Boost)	Enabled by default , can be disabled
Min. setpoint temperature	Preset at +7°C , adjustable from +7°C to +15°C
Max. setpoint temperature	Preset at +30°C , adjustable from +19°C to +30°C
Maximum duration of authorised Boost	60 minutes by default , adjustable from 30 to 90 minutes by 30 minutes steps
Max. ambient temperature for the automatic stop of the Boost	Preset at +35°C , adjustable from +25°C to +39°C
Window airing cycle duration	30 minutes by default , adjustable from 5 to 90 minutes by 5 minutes steps
Reset: return to the factory user settings	

Installer settings

Automatic window-opening detection	Enabled by default , can be disabled
PIN code locking	Disabled by default , can be enabled - Lock all controls except Boost
Reset: return to the factory user and installer settings	

Expert settings

Temperature adjustment	Ambient temperature sensor adjustment
Energy selection	Energy used by the towel rail: Electric or hydraulic
Power	Choice of the towel rail power when it is equipped with an electric cartridge
Safety: internal protection	Adjustment of the internal overheating temperature limit
Reset: return to the factory user, installer and expert settings	



Low depth once installed on the wall




Top view



Technical specifications

Dimensional and finish specifications

Height	239 mm	
Width	400 mm	
Depth	95 mm	
Color	White	Grey
Net weight	2,35 Kg	



Power supply

Operating voltage	230V AC+/-10% 50Hz
Maximum power	Self adaptive PTC nominal power 850W to 1000W according to environment & immersion heater: maximum 1500 W, resistive load
Power cord	800 mm, 3 conductors
Radio frequency	2,4Ghz

Control

Control type	Electronic PID (Proportional Integral Derivative) control
--------------	---

Environment

Protection rating	IP24 after installation under the responsibility of the integrator
Class	Class II, after installation under the responsibility of the integrator
Operating temperature	0°C to +40°C
Temperature setting range	+7°C to +30°C
Storage temperature	-20°C to +65°C
NTC electronic temperature sensor	

Applicable directives

RED	2014/53/EU
RoHS	2011/65/EU, amended by Directives 2015/863/EU and 2017/2102/EU : EN IEC 63000:2018

Normes en vigueur

RED	Safety: EN60335-1; EN60335-2-30; EN60335-2-43; EN62333 EMC: EN301489-1; EN301489-3 Radio: EN300400
RoHS	EN IEC 63000
Manufacturing	On certified site ISO 9001 V2015

Product codes

Codes	Descriptions
BXFBS2PRFA	White blower with digital controller for towel rail, RF, CLII, with 6-order pilot wire
BXFBS2PRFGA	Grey blower with digital controller for towel rail, RF, CLII, with 6-order pilot wire
RCBTHRFA	Wireless digital remote control, weekly programmable, 6 operating modes
BRETHBSA	Bracket for assembly of blower slim module, polycarbonate white, 1pce
BRETHBSTA	Bracket for assembly of blower slim module, polycarbonate translucent, 1pce
BCATHBSTA	Nut demi-spherical for blower slim assembly, polycarbonate translucent, 1pce

Product customization (style, features) possible on request. Please contact us.