



PH25




**3 in 1**  
**TRIPLE CONNECTIVITY**



## SMART AND CONNECTED COLUMN CONTROLLER TRIPLE COMMUNICATION PROTOCOL WIFI, ZIGBEE 3.0, BLUETOOTH FOR RADIATOR WITH FLUID INERTIA

Can be remotely-controlled thanks to a customizable mobile application, large full black and white screen, auto-programmable with self-learning process and dual optimization feature, occupancy detection, opened window detection, gauge and power consumption indication in kWh

### Overview

#### Main features

- Ambient temperature control
- Temperature setting
- Power On / Standby
- Operating modes selection
- Quick heating of the room using the instant Boost
- Automatic and self-learning programming, customized integrated programming or can be programmed remotely using the 6-order pilot wire

#### Application

- Electric radiator

#### Benefits

- **Modern and innovative design:** polycarbonate column with exclusive design, extra flat occupancy detector.
- **Directly connectable to the Internet** through the Internet service provider's box, without any other accessory.
- **Interoperability guaranteed** thanks to the ZIGBEE 3.0 protocol integrated into the product.
- **Can be remotely controlled** by your smartphone, tablet or PC thanks to a dedicated and customizable mobile application.
- **Excellent ergonomics of setting:** 2.09 inch backlit black and white interface easy to read, intuitive navigation and easy to use.
- **Latest generation advanced electronics** with an OTA microprocessor for software remote update.
- **«Smart» electronic control:** This means stable and accurate temperature in the room all year round.
- **Energy saving package,** comfort, performance, energy savings.
- **Auto-programming:** automatic programming by self-learning of the lifestyle.
- **Automatic changeover** summer/winter time.
- **Permanent saving of settings.**

## Functional specifications


### Use



Comfort temperature setting	Preset to <b>+19°C</b> , adjustable from +7°C to +30°C
Comfort + temperature setting	Preset to <b>+21°C</b> , adjustable from Comfort +1°C to +30°C
Eco temperature setting	Preset to <b>+15,5°C</b> , adjustable from +5°C to +19°C
Frost protection temperature setting	Preset to <b>+7°C</b> , adjustable from +5°C to +12°C
Operating modes	Auto (programming), Comfort, Comfort +, Eco, Boost, Frost protection, Holidays
Boost (only available through app)	Adjustable between 5 and 90 minutes in 5 minutes intervals: to rise quickly the temperature and turn on the heating for a time period requested
Programmable holidays mode	Frost protection for a long scheduled absence
Energy consumption gauge	Automatic indication of the level of energy consumption according to the setting temperature
Power consumption indication in kWh	Posting of the estimated amount of energy consumed in kWh since the last 24 hours or since the last reset to 0 of the energy meter



Digital commands with backlit black and white interface



<b>Opened window detection</b>	Automatic switching to Frost protection mode when a significant drop in temperature is detected
<b>Window airing feature</b>	Manual window airing can be enabled at any time
<b>Occupancy detection</b>	During an unoccupied period, the setting temperature is automatically and progressively decreased
<b>Auto-programming</b>	As soon as the device is switched on and without any initial adjustment, the device is in learning mode to understand and memorize the user's lifestyle. The integrated smart algorithm is going to analyze this information in real time in order to optimize and adapt the programme for the coming weeks
<b>Programming</b>	<ul style="list-style-type: none"> <li>- 8 different preset program profiles for each day of the week: Auto-programming, 1 comfort period, 2 comfort period, 3 comfort period, non-stop Comfort mode, non-stop Eco (economy) mode, non-stop Frost protection mode and Comfort + mode (only through app)</li> <li>- Programming assistant to help the user step by step (only through app)</li> <li>- Each day of the week can be customised (day by day or by group of days)</li> <li>- Manual and temporary overriding of a programme</li> </ul>
<b>Dual optimization feature</b>	Depending on different parameters of the room, the controller calculates and optimizes the programming of Comfort and economy periods (Eco) according to the choice of the user; Eco oriented, priority to savings or Comfort oriented, priority to comfort (by default)
<b>Help for the visually impaired</b>	<ul style="list-style-type: none"> <li>- <b>The button power on/standby mode is in relief to be easily identifiable to the touch</b></li> <li>- <b>Audible beeps indicating the change from the standby mode to active mode</b></li> </ul>
<b>Safety</b>	<ul style="list-style-type: none"> <li>- <b>Child anti-tamper:</b> touch screen locking</li> <li>- <b>Settings safety :</b> <ul style="list-style-type: none"> <li>- Min. and Max limits of the adjustment range of the Comfort setting temperature</li> <li>- Customizable PIN code locking (prevents access to the Comfort mode, advanced and expert settings)</li> </ul> </li> <li>- <b>Time, date and setting backup</b> in case the mains power supply goes off</li> <li>- <b>Internal protection against any overheating</b></li> </ul>
<b>3 levels of settings</b>	User, Advanced, Expert

## Installation

**Column holder supplied**, to be mounted directly on the radiator

**Easy to install:** Waiting position when mounting column to facilitate the connexion to the electric cartridge

Connexion to the heating cartridge by faston

## User settings

<b>Language use</b>	<b>Preset to French</b> , English available
<b>Wifi connexion</b>	<b>Direct internet connexion</b> through the Internet provider box thanks to a dedicated mobile app
<b>Backlighting</b>	<b>3 possible settings:</b> <ul style="list-style-type: none"> <li>- Reduced display with low brightness and backlighting when a button is pressed or during occupancy detection</li> <li>- Reduced display with low brightness and backlighting when a button is pressed</li> <li>- Reduced display with black screen and backlighting when a button is pressed</li> </ul>

**Return to the factory settings (user)**

## Advanced settings


<b>Occupancy detection</b>	<b>Enabled by default</b> , can be disabled
<b>Automatic window-opening detection</b>	<b>Enabled by default</b> , can be disabled
<b>Min. setpoint temperature</b>	<b>Preset at +7°C</b> , adjustable from +7°C to +18°C
<b>Max. setpoint temperature</b>	<b>Preset at +30°C</b> , adjustable from +19°C to +30°C
<b>Boost duration (only through app)</b>	<b>60 minutes by default</b> , adjustable from 5 to 90 minutes by 5 minutes steps
<b>Window airing cycle duration</b>	<b>30 minutes by default</b> , adjustable from 5 to 90 minutes by 5 minutes steps
<b>Dual optimization feature</b>	Comfort by default, Eco and Off available
<b>Connection deactivation (airplane mode)</b>	Possibility to deactivate the product connection
<b>PIN code locking</b>	Initialization - Customization - Activation and deactivation

**Return to the factory settings (user and advanced)**

## Expert settings

<b>Reduced display brightness</b>	50% by default, from 10% to 100% by intervals of 10 %
<b>Temperature adjustment</b>	Ambient temperature sensor adjustment with automatic adjustment
<b>Power setting (Used for estimation of consumption in kWh)</b>	Adjustable from 300W to 2000W by intervals of 50W
<b>Deleting connection information</b>	Possibility to delete all connection information, the product will no longer be connected

**Return to the user factory settings (user, advanced and expert)**



## Technical specifications

### Dimensional and finish specifications

Height	572 mm	
Width	91 mm	
Depth	80 mm	
Colors	White	Anthracite grey (soon)
Net weight	1.0 Kg	

### Power supply

Operating voltage	230V AC+/-10% 50Hz
Maximum power	2000W resistive load
Power cord	1200 mm, 3 conductors

### Control

Control type	Electronic	PID (Proportional Integral Derivative) control, triggered by a triac
--------------	------------	--

### Environment

Protection rating	IP24 after installation under the responsibility of the integrator
Class	Class II, after installation under the responsibility of the integrator
Operating temperature	0°C to +60°C
Temperature setting range	+7°C to +30°C
Storage temperature	-20°C to +70°C
NTC electronic temperature sensor	

### Applicable directives

RED	2014/53/EU
RoHS	RoHS 2011/65/EU, amended by Directives 2015/863/EU and 2017/2102/EU
ERP	2009/125/CE

### Normes en vigueur

RED-Sécurité	EN60335-1:2012 +A11:2014 +A13:2017+A1:2019 +A2:2019 +A14:2019 ; EN 62233:2008 ; EN60335-2-30:2009 +A11:2012+A1:2020+A12:2020
RED-CEM	ETSI EN 301 489-1 V2.2.3 (11-2019) ; ETSI EN 301 489-17 V3.2.4 (09-2020)
RED-Radio	ETSI EN 300328 V2.2.2 (07-2019)
RoHS	EN IEC 63000:2018
Manufacturing	On certified site ISO 9001 V2015

## Product code

Code	Description
COCPH25IEA	Connected right-hand column triple protocol with occupancy detection, white for radiator with fluid inertia, Class II, 80mm, 6 order-pilot wire
COCPH25IEANA (soon)	Connected right-hand column triple protocol with occupancy detection, anthracite grey for radiator with fluid inertia, Class II, 80mm, 6 order-pilot wire

Product customization (style, features) possible on request. Please contact us.