



RHDRFPRB

RADIO ROOM THERMOSTAT

Special bathroom - Programmable weekly and daily Boost Overview



Main features

- Room temperature control
- Operating modes selection
- Rapid heating of the room with the Boost
- Wireless transmission by means of radio waves

Application

- Electric towel heater
- Underfloor heating

Product + points

- **Sober design**, suitable for traditional or contemporary interiors
- **Practical**: the product has a small footprint
- **Wide display screen**, blue backlighting
- **Ergonomic setting**: 6 keys for intuitive use

Functional specifications

Use



Desired temperature	Adjustable from +5°C to +30°C
Operating modes	Auto-Comfort, Eco, Frost protection, Prog, Heating on standby mode
Boost function	<ul style="list-style-type: none"> - Manual Boost: temperature setpoint is raised up at maximum during the selected time, adjustable between 10 and 60 minutes by 10 minutes step - Programmable Boost: until 2 programmed Boost independently for each day of the week - Deferred Boost: to choose the next Boost period start time
Safety	<ul style="list-style-type: none"> - Child safety: keypad locking - Settings safety: <ul style="list-style-type: none"> - Restricted settings in respect of a minimum temperature setpoint - Restricted settings in respect of a maximum temperature setpoint
Display screen	Viewing of settings, of measured and set temperatures, the pairing process, of wireless transmission, keypad locking and of battery status

Installation

2 fitting options: on a junction box or salient

Pairing with a wireless 1-channel receiver (integrated into a towel heater) and/or a wireless multi-channel central control unit for underfloor heating/cooling, verification of pairing

Wireless transmission by means of radio waves: Reliability, performance, flexibility and modularity



Approved Europe-wide, highly resistant to external sources of interference

Signals can go through walls and ceilings

The wireless aspect means that you can change the lay-out of areas without having to make any changes at all to wiring

Advanced settings

Language	English, French, Italian or German
Temperature unit	Degrees Celsius or degrees Fahrenheit
Max. setpoint temperature	Preset to +28°C , adjustable from +5°C to +30°C
Min. setpoint temperature	Preset to +7°C , adjustable from +5°C to +30°C
Eco temperature decrease	Preset to -3,5°C , adjustable from -0,5°C to -7°C
Frost protection temperature	Preset to +7°C , adjustable from +5°C to +12°C
Temperature adjustment	Ambient sensor calibration
Restoring factory settings	5 secondes minimum to restor factory settings



Technical specifications

Dimensional and finish specifications

Height	99 mm
Width	90 mm
Depth	23 mm
Color	Blanc RAL 9010
Net weight	0,2 Kg

Power supply

2 1.5V AAA / LR06 alkaline batteries	Battery life approximately 2 years
--------------------------------------	------------------------------------

Control

Control type	On/off - PID
--------------	--------------

Radio-wave transmission

Frequency	Radio transmitter, frequency 868.3 Mhz. Can be used throughout Europe
Transmission	Every 10 minutes, at the latest 1 minute after a set temperature change

Environment

Protection rating	IP20
Class	Class III
Control class and energy contribution	IV according ERP/2009/125/EC and associated regulations
Operating temperature	0°C to +40°C
Temperature setting range	+5°C to +30°C
Storage temperature	-10°C to +50°C
Max. humidity level	80% at +25°C (without condensation)

Applicable directives

RED	2014/53/EU
RoHS	2011/65/EU, amended by Directives 2015/863/EU and 2017/2102/EU

Applicable standards

RED	2014/53/EU
Article 3.1a (Safety)	EN60730-1/ EN60730-2-9/ EN62311
Article 3.1b (EMC)	ETSI EN 301489-1 V1.9.2 / ETSI EN301489-3
RoHS	EN IEC 6300
Manufacturing	On certified site ISO 9001 V2015

This device has an intermittent timer conforming to standard EN 12098-5.

Product codes

Codes	References
RHDRFPFB	Special bathroom programmable weekly boost thermostat

Product customization (design features) possible. Please contact us.